

Trade name : UV-PU Insulation Coat

Status : 01.01.2007

Product no. : 471 331 0000

Version : 1 / D

Date of printing : 01.01.2007

1.) Identification of the substance/preparation and company

Product details

Trade name

UV-PU Insulation Coat

Identification of the manufacturer / supplier

Address

Shanghai Treffert Special Coatings Co.Ltd.
No. 1299, Beihe Road, Jiading North Industrial Zone,
201807 Shanghai
Telephone no. (+86)-21-5165-1818
Fax no. (+86)-21-5165-1388

Information provided by / telephone

Laboratory +86-21 5165 1818 (ext. 836)

Emergency telephone number

+86-21 5165 1818

Use

Industrial Wood Coatings

2.) Composition / information on ingredients

Hazardous ingredients

Ethanol, 2-buthoxy

CAS no.	111-76-2		
Concentration	>= 1	< 5	%-b.w.
Classification	R10		

N-Buthanol

CAS no.	71-36-3		
Concentration	>= 1	< 5	%-b.w.
Classification	R10		

3.) Hazards possibilities

Unstable (reactive) upon depletion of inhibitor.

4.) First aid measures

General information

Seek medical advice immediately.

After inhalation

Ensure supply of fresh air. In the event of symptoms take medical treatment.

After skin contact

Wash off immediately with soap and water.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Remove contact lenses; In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

After ingestion

Take medical treatment. Do not induce vomiting.

Trade name : UV-PU Insulation Coat

Status : 01.01.2007

Product no. : 471 331 0000

Version : 1 / D

Date of printing : 01.01.2007

5.) Fire-fighting measures

Suitable extinguishing media

Water; Product itself is non-combustible; adapt fire extinguishing measures to surrounding areas.

Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases

None known

Special protective equipment for fire-fighting

In case of combustion use a suitable breathing apparatus.

Other information

Fire residues and contaminated fire-fighting water must be disposed of in accordance with the local regulations.

6.) Accidental release measures

Personal precautions

Remove persons to safety. Keep away sources of ignition.

Environmental precautions

Cover drains. In case the product spills into sewage waters, immediately inform the authorities.

Methods for cleaning up/taking up

Pick up with absorbent material. Clean contaminated surfaces thoroughly with water. Dispose of absorbed material in accordance with the regulations.

Additional informations

Information regarding Safe handling, see chapter 7.

7.) Handling and storage

Handling

Advice on safe handling

Use only in well-ventilated areas.

Advice on protection against fire and explosion

The product is not combustible. Substance/product is self-extinguishing but can burn together with flammable materials.

Use

Industrial Wood- and Foilcoatings

Storage

Further information on storage conditions

-Sensitive to frost- Keep container in a cool, well-ventilated place. Protect from extreme heat and cold. Recommended storage temperature: 10 - 25 °C.

8.) Exposure controls / personal protection

Additional hints on technical system design.

See chapter 7; no measures exceeding the ones mentioned are necessary.

Ingredients with occupational exposure limits to be monitored

N O N E

Personal protective equipment

Hand protection

In case of intensive contact wear protective gloves.

Appropriate Material

Natural Latex

Inappropriate material

Leather